

# **Geology Architecture Mapping of the Abbotsford-Sumas Aquifer**

Jacek Scibek (presenting), Aparna Desphande, Diana M. Allen, Nadine Schuurman, and Basil Hii

Dr. Diana Allen Jacek Scibek

Department of Earth Sciences Simon Fraser University, Burnaby, BC



Dr. Nadine Shuurman Aparna Dushanbe

Department of Geography Simon Fraser University, Burnaby, BC

Basil Hii

**Environment Canada** 

#### **OUTLINE:**

- 1. Study objectives
- 2. Abbotsford-Sumas aquifer
- 3. Litholog sources and standardization process
- 4. Unique challenges in acquiring and integrating Canadian and US datasets
- 5. Progress in development of architecture of the Abbotsford-Sumas aquifer

#### **OBJECTIVES:**

- mapping aquifer architecture (Abbotsford-Sumas aquifer)
- generate layers for numerical models (flow and transport)
- make best use of limited & low quality data
- standardize & integrate US and Canadian data
- ongoing research at Simon Fraser University and Environment Canada

#### **MODEL APPLICATIONS:**

- regional transport model (contaminants)
- local smaller-scale models
- predict effects of land use scenarios on groundwater quality & quantity
- climate change impact scenarios (water resources)

Fraser Valley and Abbotsford-Sumas Aquifer: Surficial Geology




#### **LITHOLOG SOURCES:**

# Washington State

- Dept of Ecology (WRIA 1 database)
- NWIFC (Northwest Indian Fisheries Commission)

#### **British Columbia**

- BC Ministry of Water Land and Air Protection
- BC Ministry of Energy and Mines (deep boreholes)
- Geological Survey of Canada Papers
- BC Ministry of Transportation (bridge construction sites)
- Drill Core logs various projects






Aquifers and Water Wells of British Columbia



About Layers Legend Find Location Refresh Map Disclaimer




# How to convert raw lithology data ...


			1111		<b>—</b>	
Depa Secor	Original and First Copy wit irtment of Ecology nd Copy — Owner's Copy d Copy — Driller's Copy	WATER WE	VASHINGTON Permit No.	10		
	OWNER: Name		Address Sumas	1 W	A	
	LOCATION OF W		_ <b>SE</b> , Sw, sec. T		4. wм	
(3)	PROPOSED USE:	Domestic 💢 Industrial 🗀 Municipal 🗀	(10) WELL LOG:			
		Irrigation  Test Well Other	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ci	THE MILLERIC	Tr bit CUCL	
(4)	TYPE OF WORK:	Owner's number of well (if more than one)	MATERIAL	FROM	TO	
	New we		Topsoil	0	2.	
	Deepend	cd Cable Driven Driven Cable Driven Driven Cable Driven Cable Driven Cable Driven Driven Cable Driven D	Brown small gravel	2	8	
	Recondi	noned	Brown clay and sand	8	12	
(5)	DIMENSIONS:	Diameter of well	Gray clay, some sand	12	18	
	Drilled 100 ft.	Depth of completed well. 63	Gray sand & some gravel, water	18	29	
	CONCEDITORION	DETAILS.	Brown clay	29	31	
(6)	CONSTRUCTION	24 PASS 7-12-1	Gray clay	31	33	
	_	6 Diam. from +2 to 53 tt	Gray sand and some gravel, water	33	37.	
		" Diam. from ft. to ft ft.	Gray clay	37	53	
	Welded 🖟	Diam. from the to	Gray we sand & water, some gravel	53	63	
	Perforations: Yes	No □X	Gray clay, some sand - lots of			
	Type of perforator	used	wood	63	68	
		nsin. byin.	Gray sand and some wood - water	68	<u>83</u>	
		ations from ft. to ft.	Gray fine dirty sand - water	83		
		ations from ft. to ft.				
	Manufacturer's Nat	Johnson  less Steel Model No	6 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -			

... to 3D database ...

# ... to hydrostratigraphic models ...



# ... to groundwater flow model




# **Canadian Database Data acquisition**

- drill well reports submitted to government (not mandatory)
- online well registration system free information but poor data quality
- lithology, location, well attributes


#### LITHOLOG STANDARDIZATION:

BCGS 082E008421 # 1 wtn 000000076552 UTM Zone 11 Easting Northing UTM Code From 6 To 7 Ft. BROKEN ROCK MOIST CLAY Seq# 2 Water Depth 3.4 Yield 30 Gallons per Hour (U.S./Imperial) Screen from to PT BCGS 082E008421 # 1 wtn 000000076552 UTM Zone 11 Easting Northing UTM Code From 0 To 6 Ft. BROWN SAND & GRAVEL COBBLES Seq# 1 Water Depth 3.4 Yield 30 Gallons per Hour (U.S./Imperial) Screen from to PT



coarse gravel and silt
clean coarse sand and small w b gravel
very coarse sand/ coarse gravel and fine silt
coarse sand and med sand
med sand/ thin clay layers and some boulders
med and coarse sand/ fine sand and silt
coarse gravel with clay layers
coarse sand and some gravel
medium sand with pebbles
gravel/ some sand
very coarse gravel/ very little sand

[WTN]	[layer num]	[layer class]	[depth (top of layer)]	[depth (bottom of layer)]	[thickness]	[material(1)]	[modifier]	[size]	[color]	[structure]	[material(2)]	[modifier]	[size]	[color]	[structure]	[material(3)]	[source text]
5156	1		0	4	4	till	Ц										till
5156	2		4	30		cobbles					gravel		- 1				cobbles and gravels
5156	3		30	78		clay					silt				strip	s	clays and silt strips
5156	4		78	90		gravel		coars	e		sand		10				coarse gravels and sands
186	- 1		0	35.6	35.6			0.0000									dug
86	2		35.6	41		sand		coars	e								coarse sand
√ \86	3		41	50	9	sand					clay						sand and clay
5186	4		50	55	5	sand											sand
5186	5		55	62	7	sand					gravel						sand and gravel (wb)
5186	6		62	63.6	1.6	sand		medi	um-co	arse							med coarse sand
5280	1		0	8	8	silt							11				surface silts
5280	2		8	26	18	gravel		coars	e								heavy gravels
5280	3		26	34		clay			browi	n							brown clay
5280	4		34	36.5		gravel	11										gravel
5280	5		36.5	60		clay					silt						clay and varied silts
5280	6		60	83		gravel		medi	um		sand	fine					medium gravels with fine sands
7863	1		0	55		gravel					sand	dry					gravel sand - dry
7863	2		55	76		sand					gravel	son					sand - some gravel - water - bearing
7863	3		76	78		sand			grey		clay						gray sand with clay
7869	1		0	5		soil					sand						topsoil - sand
7869	2		5	7		sand					gravel						sand/ gravel
7869	3		7	23		sand					gravel					cobbles	sand/ gravel/ cobbles
7869	4		23	44		sand					silt			i	n sa		silty sand
7869	5		44	59		sand	dirty										sand dirty
7869	6		59	66		sand	1 800				gravel						sand/ gravel
7869	7		66	81		sand		fine			silt		- 1	- li	n sa	and	sand fine & silty
7869	8		81	91		silt		10000			, T. O. T. O					1000	silt
7869	9		91	104		sand	clear	medi	um								medium sand clean
7869	10		104	115		silt			7.11.0								silt
7887	1		0	4		soil					gravel						top soil with gravel
7887	2		4	12		gravel					cobbles						gravel & cobbles
7887	3		12	17		sand					gravel						sand & gravel
7887	4	-	17	33		sand		medi	ım fir		gravel		- 17				medium & fine sands with gravel
7887	5		33	37		sand	wet	mean			gravel		- 17				moist sand & gravel
7887	6		37	70		sand	wot				gravel		- 1			silt	water - bearing silty sand with gravel
7887	7		70	78		sand	-				gravel					O.III	cleaner sand with gravel/ water - bearing
7926	1		0	47		silt	-				cobbles	7 0	- 0		n si	l+	COBBLED SILTS
7926	2		47	66			harde	on			connies	7 11			11.51	IL 3	HARDPAN
7320	- 2		47	מט	19	silt	hardp	ıdii									HARDEAN



#### **B.C. LITHOLOG STANDARDIZATION:**

raw data → LDBuilder → Access DB

one record / litho unit in each litholog

relational DB approach

well ID & layer elevation as keys

separate tables for lithology, location, attributes

## **B.C. LITHOLOG STANDARDIZATION:**

# **Training standardization filter (time consuming):**

- raw data has > 6000 unique sediment descriptions
- first pass produced >100 sediment categories
- review standards
- second pass produced 36 sediment categories
- treat bedrock (e.g. fractures) separately

#### **DATABASE INTEGRATION CHALLENGES:**

- 1) semantics in lithologs
  - different level of detail

- 2) classification schemes
  - digitize paper forms & scanned images (e.g. Dept Ecology)
  - different well ID's

3) scale of the study area

## **DATABASE INTEGRATION CHALLENGES:**

#### Schematic differences:

- 3 tables in Canadian DB: Lithology, General (address), UTM
- 4 tables in US DBs: Recovery, Material (lithology), Test (hydraulic),
   WellData (address)

#### Database structure:

- Canadian DB geology one field, US db. 3 fields (3 materials)
- different field names for same attributes (difficult to decipher metadata)

#### Semantic difference:

- Canadian db. standard 36 categories
- US db. 21 descriptors in 3 different fields (180 unique categories when 2 fields combined)
- reduced US db. to 36 categories prior to integration with Canadian db.

# **DATA QUALITY PROBLEMS:**

#### Location:

- coordinates not available for many wells
- coordinates and elevation inaccurate
- get some coordinates from well address and Street
   Network files

# Geology lithologs

- text file output not formatted correctly
- max 24 layers per litholog
- ground elevation often recorded as 0
- missing uppermost unit
- conversion of depths to elevations

# **DATA QUALITY PROBLEMS:**

# Quality depends on:

- driller's education and experience
- amount of detail reported to government database
- transcription errors
- type of sediments, method of drilling ...

"cryptic" litholog example:

Water bearing sand and gravel S/L 53'
Up to here look at Mr. \_\_\_\_\_'s room'
Whatcom
Stoney Clay


## LAYERED HYDROSTRATIGRAPHY:


- 1) create cross-sections from standardized lithologs
- 2) generalize layers
- 3) digitize layer boundaries and construct surfaces
- 4) tie surfaces to valley walls


## LAYERED HYDROSTRATIGRAPHY:


#### Problems:

- heterogeneity of glacial deposits
- correlation of lithologies
- lack of deep boreholes
- large GIS workload time costs










Produced by: Apama Deshpande

Dept. of Geography Simon Fraser University Bumaby

Canada

Cross Section GG'

Geology Architecture Mapping Of the Abbotsford-Sumas Aquifer




Produced by: Apama Deshpande Dept. of Geography Simon Fraser University Vindow Bumaby

Canada

Geology Architecture Mapping of the Abbotsford-Sumas Aquifer

Cross Section SS'



Produced by: Apama Deshpande Dept. of Geography Simon Fraser University Bumaby

Canada

Geology Architecture Mapping of the Abbotsford-Sumas Aquifer

Cross Section KK'